



Desengordurante S T600

Desengordurante S T600 is a cleaning and degreasing agent with no CHC for all metallic and polymeric supports. It can also be used in the degreasing of plastic materials, in particular to eliminate release agents. It can be applied by brush, paint-brush, sponge or by spraying.

Colour	Colourless		
Application Method	Soak a clean, dry cloth with Desengordurante Timicor Solvente . Clean small surfaces (about 0,5 m ²) at a time and then wipe with another cloth, clean and dry. As appropriate, replace 2 or 3 times the cloth during cleaning. Do not leave the Desengordurante Timicor Solvente dry on the surface. Failure to perform the degreasing operation may cause paint defects such as: total or partial loss of adhesion and the formation of blistering. It is always necessary to clean the surface with the Desengordurante Timicor Solvente before and after sanding and painting.		
Hardener			
Thinning	No thinning		
Viscosity Application			
Application	Spray Pressure	Spray Nozzle	Number of Coats
Application Spray			
Airless / Airmix			
Pot Life			
Dry Film Thickness			
Flash Off			
Sanding			
Drying at 20 °C Drying at 60 °C			
VOC	The maximum VOC limit set by the EU for this product (product category: IIA / a) in its ready-to-apply form is max. of 850 g / liter VOC. The maximum VOC content of this product ready to apply is at most 743 g / liter.		
Shelf Life	When stored inside in original containers and sheltered from sunlight and cold at temperatures between 5 and 40°C, the product has a shelf life of 3 years after its date of manufacture.		
Observations			

This technical data sheet is merely of an advisory nature, based on current technical know-how, for guidance, and may be changed without prior notice. As the conditions are beyond our control, the company cannot under any circumstances be held responsible for the obtained final results in its use.