



Desengordurante WBC T610

Product for degreasing several metal supports and paint products. It can also be used in the degreasing of plastic materials, in particular to eliminate release agents.

Colour	Colourless		
Application Method	<p>Soak a clean, dry cloth with Desengordurante WBC. Clean small surfaces (about 0,5 m²) at a time and then wipe with another cloth, clean and dry. As appropriate, replace 2 or 3 times the cloth during cleaning. Do not leave the Desengordurante WBC dry on the surface.</p> <p>Failure to perform the degreasing operation may cause paint defects such as: total or partial loss of adhesion and the formation of blistering. It is always necessary to clean the surface with the Desengordurante WBC before and after sanding and painting.</p>		
Hardener			
Thinning	No thinning		
Viscosity Application			
Application	Spray Pressure	Spray Nozzle	Number of Coats
Application Spray			
Airless / Airmix			
Pot Life			
Dry Film Thickness			
Flash Off			
Sanding			
Drying at 20 °C Drying at 60 °C			
VOC	The maximum VOC limit set by the EU for this product (product category: IIA / a) in its ready-to-apply form is max. of 200 g / liter VOC. The maximum VOC content of this product ready to apply is at most 195 g / liter.		
Shelf Life	When stored inside in original containers and sheltered from sunlight and cold at temperatures between 5 and 40 °C, the product has a shelf life of 3 years after its date of manufacture.		
Observations	Do not use Desengordurante WBC on polyester body filler due to the high sensitivity to water.		

This technical data sheet is merely of an advisory nature, based on current technical know-how, for guidance, and may be changed without prior notice. As the conditions are beyond our control, the company cannot under any circumstances be held responsible for the obtained final results in its use.