



## Diluyente 2K Rápido T410

**Diluyente 2K Rápido T410** is a thinner based on a mixture of organic solvents and selected esters to allow good solubility of all “auto acrylic root” products, with a fast evaporation rate, especially suitable for use in small touch-ups whenever faster drying is desired. For more information on typical or ideal levels of use and for more precise details, please refer to our technical data sheets for the basing products.

Colour	Colourless		
Mixing Ratio			
Hardener			
Thinning			
Viscosity Application			
Application	Spray Pressure	Spray Nozzle	Number of Coats
Application Spray			
Airless / Airmix			
Pot Life			
Dry Film Thickness			
Flash Off			
Sanding			
Drying at 20 °C Drying at 60 °C			
VOC			
SHELF LIFE	When stored inside in original containers and sheltered from sunlight and cold at temperatures between 5 and 40 °C, the product has a shelf life of 3 years after its date of manufacture.		
Safety Instructions	Keep containers tightly closed and away from heat sources, flame or other potential sources of ignition. The preparation may contain static electricity. Always use grounding lines when transferring from a container to another. All empty containers and packaging must be disposed in accordance with local and national regulations and legislation. Protect your environment!		
This technical data sheet is merely of an advisory nature, based on current technical know-how, for guidance, and may be changed without prior notice. As the conditions are beyond our control, the company cannot under any circumstances be held responsible for the obtained final results in its use.			