



Endurecedor Timiperfection

Endurecedor Timiperfection is a hardener based on a mixture of organic solvents and esters, with aliphatic isocyanates selected to allow good catalysis of all products in our **Timiperfection** range. For more information on typical or ideal levels of use and for more precise details, please refer to our technical data sheets for the basic products.

Colour	Colourless		
Mixing ratio			
Hardener			
Thinning			
Viscosity Application			
Application	Spraying Pressure	Spraying Nozzle	Number of coats
Application Spray			
Airless / Airmix			
Pot Life			
Dry film thickness			
Flash Off			
Sanding			
Drying at 20 °C Drying at 60 °C			
VOC			
Shelf Life	When stored inside in original containers and sheltered from sunlight and cold at temperatures between 5 and 40°C, the product has a shelf life of 3 years after its date of manufacture.		
Safety Information	Keep containers tightly closed. Keep containers cool from heat, flame, or other potential sources of ignition. The preparation may have static electricity. Always use grounding lines when transferring from one container to another. All empty containers and packaging must be disposed of in accordance with local and national regulations and legislation. Protect your environment!		

This technical data sheet is merely of an advisory nature, based on current technical know-how, for guidance, and may be changed without prior notice. As the conditions are beyond our control, the company cannot under any circumstances be held responsible for the obtained final results in its use.