



TIMIFENDAS – Filling Mass

DESCRIPTION

Timifendas is a water based filling mass of a vinylic copolymer and 100% acrylic water based, white pigments and inert loads, ready to be applied. With filling power and indoor surfaces levelling, such as walls and ceilings over almost all types of surface allowing a surface with good conditions to final finish proceeding.

PROPERTIES

- Great ease of application
- Good filling power
- High hardness after drying
- Great resistance
- Good sanding which allows a better surface levelling

PHYSICAL DATA

COLOUR		White
FILM ASPECT	Gloss	Matt
SPECIFIC GRAVITY		2,00 ± 0,05 g/cm ³
VISCOSITY		850 ± 50 Poises
SOLIDS BY WEIGHT		83 % – Theoretical Value

APPLICATION DATA

SURFACE PREPARATION

The existing holes, cracks, gaps, etc. must be properly cleaned in order to free them from dust or poorly adhered products. Cracks or gaps larger than 5 mm must be previously filled by layers. All surfaces must be dry, free of grease, dust and other contaminants.

Previously limewashed, powdery or friable renders – Apply one coat of **Timisolador Acrílico Incolor** beforehand.

APPLICATION METHOD

Spatula

THEORETICAL COVERAGE

1-2 Kg/m² (depending on the surface and application conditions)

DRYING TIME

Hardening – 24 hours (depending on the surface and the applied layer)

UTENSILS/TOOLS CLEANING

The utensils/tools must be cleaned with **Water** immediately after the application.

This technical data sheet is merely of an advisory nature, based on current technical know-how, for guidance, and may be changed without prior notice. As the conditions are beyond our control, the company cannot under any circumstances be held responsible for the obtained final results in its use.

ENVIRONMENTAL CONDITIONS DURING APPLICATION

Ambient Temperature	≥ 5 °C
Relative Humidity	≤ 90 %
Surface Temperature	2 to 3 °C above dew point

SHELF LIFE

When stored inside in original containers and sheltered from sunlight and cold at temperatures between 5 and 40 °C, the product has a shelf life of 3 years after its date of manufacture.

OBSERVATIONS

To avoid the appearance of stains due to differences in absorption, it is suitable to insulate the repaired areas with **Timifendas**, with a suitable Primer coat.

HEALTH, SAFETY AND ENVIRONMENT

In general, avoid contact with eyes and skin; gloves, goggles and appropriate clothing must be worn. Keep out of the reach of children. Use only in well ventilated areas. Do not empty into drains. Keep the container properly sealed and stored in the correct place. Take correct measures when transporting the product; Prevent any accident or incident that may occur during transportation, in particular the rupture or deterioration of the packaging. Ensure that the container is correctly stacked in a safe area. Do not store or use the product in extreme temperature conditions always between 5 and 40 °C. Always take account of the appropriate legislation relating to the Environment, Hygiene, Health and Safety at Work. For more information it is essential to read the label on the container and the product Material Safe Data Sheet.