



TIMICRYLTEX – Sand Acrylic Paint Ext./Int.

DESCRIPTION

TIMICRYLTEX is a water-based paint 100 % acrylic, selected loads and pigments, providing high quality finishes and decorative beauty with matt-fine sand textured look. It is available in catalogue colours (5010-5080) and in the system **Pro Mix 1,2** and **3**. Its high resistance properties to weather and ultraviolet rays connected with good water vapor permeability allow a much longer paint life than conventional paints. It is suitable for all types of exterior walls, on the most varied type of substrates, plaster sanded and smooth, concrete, cement, brick, synthetic stuccos, tinned and others, in new paintings or repainting of conventional smooth plastic paints, non-glosses.

PROPERTIES

- Good applicability
- Good coverage and whiteness
- Excellent durability, maintains original film appearance over a long period
- Allows the application of high thicknesses per coat hiding small imperfections and covering static micro-cracks, typical of new renders
- Excellent water resistance
- Resistant to dirt retention
- Excellent film resistance to the growth of fungi and algae

PHYSICAL DATA

COLOUR		White and others
FILM ASPECT	Gloss	Matt – Fine Sand Textured
SPECIFIC GRAVITY		1.570 ± 0.050 g/cm ³
VISCOSITY		125 - 135 KU
SOLIDS BY WEIGHT		70 % – Theoretical value

APPLICATION DATA

SURFACE PREPARATION

All surfaces must be dry, firm, free of grease, dust and other contaminants.

New surfaces – Over friable or dusty surfaces, after brushing, apply a coat of **Timisolador Acrílico Branco**. Over alkaline surfaces, apply a coat of **Timisolador Acrílico Incolor**. Over plasterboard and projected stucco, apply a coat of **Primário Praimicryl** or **Timisolante Aquoso Branco**.

Previously painted surfaces

Outdoors – Perform a wash with the aid of a under pressure water jet and let dry; repair damaged areas and proceed as for new surfaces. If the previous paint is chalky, apply one coat of **Timisolador Acrílico Incolor**.

Previously lime washed surfaces – Brush carefully. If possible wash down with the aid of a under pressure water jet, let dry and apply a coat of **Timisolador Acrílico Incolor**.

New cement renders – Wait for complete cement cure, which takes approximately 28 days. The cement rendering must be dry, firm, clean, free of grease, dust and other contaminants. Brush if needed, to remove non-adherent loose particles. Apply a coat of **Primário Praimicryl** or **Timisolante Aquoso Branco** and let it dry.

Previously painted cement renders – Clean up the area with the aid of a under pressure water jet, brush to remove non-adherent old loose paint. Repair damaged areas and cracks with dimensions between 0,3 and 1,0 mm. In the areas where the cement renders are displayed proceed as indicated as the above line “new cement renders”.

This technical data sheet is merely of an advisory nature, based on current technical know-how, for guidance, and may be changed without prior notice. As the conditions of application are beyond our control, the company cannot under any circumstances be held responsible for the obtained final results in its use.



TIMICRYLTEX – Sand Acrylic Paint Ext./Int.

APPLICATION CHARACTERISTICS

APPLICATION METHOD	Brush, anti-spatter roller and foam roller
THEORETICAL COVERAGE	6 to 8 m ² /L/Per coat
DRYING TIME	Touch dry – 1 at 2 hours Repainting – 10 at 12 hours
THINNING	No thinning, ready to use
APPLICATION	Apply two to three coats of Timicryltex
UTENSILS/TOOLS CLEANING	The utensils/tools must be cleaned with water immediately after the application.

ENVIRONMENTAL CONDITIONS DURING APPLICATION

Ambient Temperature	≥ 5 °C
Relative Humidity	≤ 80 %
Surface temperature	2 to 3 °C above dew point

SHELF LIFE

When stored inside in original containers and sheltered from sunlight and cold at temperatures between 5 and 40 °C, the product has a shelf life of 3 years after its date of manufacture.

SPECIAL NOTE

Due to the fact that this coating be applied in a relatively high layer (thick), its only acquires resistance to rain after 24 hours.

Full layers must always be applied, taking care, when necessary interrupt the work, doing it in corners, edges or areas to avoid the formation of splices and layer overlap.

This paint was specially formulated to have less sensitivity to the appearance of sweating (snail slime) when application and drying occurs with severe environmental conditions (low temperature, high humidity and with conditions favourable to high condensations).

HEALTH, SAFETY AND ENVIRONMENT

In general, avoid contact with eyes and skin; gloves, goggles and appropriate clothing must be worn. Keep out of the reach of children. Use only in well ventilated areas. Do not empty into drains. Keep the container properly sealed and stored in the correct place. Take correct measures when transporting the product; Prevent any accident or incident that may occur during transportation, in particular the rupture or deterioration of the packaging. Ensure that the container is correctly stacked in a safe area. Do not store or use the product in extreme temperature conditions always between 5 and 40 °C. Always take account of the appropriate legislation relating to the Environment, Hygiene, Health and Safety at Work. For more information it is essential to read the label on the container and the product Material Safe Data Sheet.

This technical data sheet is merely of an advisory nature, based on current technical know-how, for guidance, and may be changed without prior notice. As the conditions of application are beyond our control, the company cannot under any circumstances be held responsible for the obtained final results in its use.